






LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Type N PFA Iso-Flat Pair Thermocouple Cable / Fil (IEC)



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Type N PFA Isolé Flat Pair Thermocouple Câble / Fil (IEC)

PFA Téflon® paire plate isolée. PFA Téflon® a une bonne résistance mécanique et une bonne flexibilité, résistant aux huiles, acides et autres fluides nocifs, gaz, vapeur et pression.

Spécifications
Specifications

General Description	Resistant to oils, acids other adverse agents and fluids. Good mechanical strength and flexibility. PTFE better for steam/elevated pressure environments.
Cable Length	10m, 25m, 50m, 100m
Cable Type	Single pair of PFA insulated conductors, laid flat with PFA jacket
Core / Strands	7/0.2mm
Conductor Cross Section 7/0.2 (mm²)	0.219
Outer Colour	Pink
+ Colour	Pink
- Colour	White
Drain Wire	No
Insulation Material	PFA Insulated
Loop Resistance 7/0.2 (Ohms per combined metre)	6.2
Max. Temperature	+260°C
Min. Temperature	-75°C



+ Conductor	Nicrosil
- Conductor	Nisil
Screen	No
Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	N
Tolerance	Class 1